



## Failure Analysis of CLT Shear Walls with Opening Subjected to Horizontal and Vertical Loads

<https://research.thinkwood.com/en/permalink/catalogue1655>

Author: Yasumura, Motoi  
Kobayashi, Kenji  
Okabe, Minoru

Year of Publication: 2016

Country of Publication: Austria

Format: Conference Paper

Material: CLT (Cross-Laminated Timber)

Application: Shear Walls

Topic: Mechanical Properties

Keywords: Opening  
FEM  
Horizontal Loading  
Failure

Language: English

Conference: World Conference on Timber Engineering

Research Status: Complete

Notes: August 22-25, 2016, Vienna, Austria  
p. 3555-3562

### Summary:

CLT wall panels having an opening were subjected to horizontal loading and the failure process of CLT around the opening was compared with the simulation by Finite Element Method. Three types of CLT wall panels of 3500mm length and 2700mm height had an opening of 1500mm length and 900mm to 2000mm height at the center of the wall panel. During the racking test of wall panel cracks appeared at the corner of the opening. The wall panel was modelled with three models. One included a single orthotropic plane element calculated from the mechanical properties parallel and perpendicular direction of lamina layout (Model I). Another included two orthotropic plane elements crossed each other and connected at each nodal point based on the mechanical property of lamina composing the panel (Model II). The third model included laminae of 30-by 120mm cross section arranged vertical and horizontal directions (Model III). The simulation by each model predicted comparatively well the initial shear stiffness of CLT wall panels and the initiation of cracks at the corner of opening.

Online Access: Free

### Resource Link

<http://hdl.handle.net/20.500.12708/172>

