





## Wind-Induced Vibration of Tall Wood Buildings

<https://research.thinkwood.com/en/permalink/catalogue1105>

Author: Reynolds, Thomas  
Chang, Wen-Shao  
Harris, Richard

Organization: TRADA

Year of Publication: 2011

Country of Publication: United Kingdom

Format: Report

Material: Glulam (Glue-Laminated Timber)  
CLT (Cross-Laminated Timber)

Application: Wood Building Systems

Topic: Wind  
Connections

Keywords: Across-Wind Vibration  
Turbulence  
Along-Wind Vibration  
Vortex Shedding

Language: English

Research Status: Complete

### Summary:

Wind-induced vibration is an important design consideration in tall buildings in any structural material. The two main forms of wind-induced vibration - across-wind vibration due to vortex shedding and along-wind vibration due to turbulence - were taken into consideration when undertaking this study. Both types are addressed in Eurocode 1.

This research summary discusses a study which, following a sensitivity study into the effect of stiffness and damping on wind-induced vibration, addresses a shortfall in current knowledge of stiffness in dowel-type connections. This type of connection is found in the glulam frame and CLT structures currently at the forefront of tall timber construction, and its behaviour was investigated by measuring and analysing stiffness and damping under oscillating loads representative of wind-induced vibration.

This research summary covers a number of factors relating to wind-induced vibration which must be considered when constructing a tall timber building, such as how to assess connection stiffness under in-service vibration. The various conditions were then applied to a case study - the proposed Barentshaus building.

Online Access: Payment Required

### Resource Link

<https://www.trada.co.uk/publications/research-summaries/wind-induced-vibration-in-tall-timber-buildings/>